



### P.B.O. narrow tapes

These tapes are woven with PBO (Zylon) yarns.

Available in different widths, generally between 40 et 300 mm and a thickness between 2 and 5 mm.

They are woven in one or several layers.

---

### Applications

- Stacker bars cover
- Narrow conveyor
- They can also be used for the manufacture of suction pads

Their composition and construction make them resistant to high temperature, prevent from marking and from thermal shocks

---

### Thermal properties

550° to 650°C: decomposition of the PBO fiber

### Chemical properties

<u>Resistance</u>	<u>P.B.O.</u>
-------------------	---------------

Acid:	good
-------	------

Base:	good
-------	------

Solvent:	good
----------	------

### Physical properties

<u>P.B.O.</u>
---------------

UV resistance:	low
----------------	-----

### Product specifications (example of one dimension)

<u>Width</u>	<u>Thickness</u>	<u>Weight / meter</u>
50 mm	2,5 mm	+/- 50 g/m

Packaging in rolls of 50 m  
Other dimensions: please contact us

### Our address:

Ferlam Technologies  
85, rue Monge  
BP 317  
59056 Roubaix cedex 1  
France

Tél: + 33 (0)3 20 65 96 96  
Fax: + 33 (0)3 20 65 96 99  
Web site: [www.ferlam.com](http://www.ferlam.com)  
Contact: [info@ferlam.com](mailto:info@ferlam.com)