



Dense aramid narrow tapes

Dense aramid tapes are available in width generally below 15 mm.

They are woven with yarns, without wire reinforcement.

Applications

Conveying cylinders cover in the flat glass industry
For this specific use, the tapes prevent the glass from touching the rollers. They resist to high temperature and prevent from thermal shocks.

The construction of the product makes it particularly abrasive-resistant.

These aramid tapes can also be used on guiding bars in the hollow glass industry.

... / ...

Thermal properties

450° to 500°C, decomposition of para-aramid fiber

Chemical properties

<u>Resistance</u>	<u>Para-aramid</u>
Acid:	low
Base:	low
Solvent:	good

Physical properties

	<u>Para-aramid</u>
UV resistance:	low
Dielectric strength:	---

Product specifications (example of some dimensions)

<u>Width</u>	<u>Thickness</u>	<u>Weight / meter</u>
13 mm	2,0 mm	+/- 15 g/m
13mm	3,0 mm	+/- 25 g/m

Packaging: in rolls or bobbins
Other dimensions: please contact us

Our address:

Ferlam Technologies
85, rue Monge
BP 317
59056 Roubaix cedex 1
France

Tél: + 33 (0)3 20 65 96 96
Fax: + 33 (0)3 20 65 96 99
Web site: www.ferlam.com
Contact: info@ferlam.com