



Stainless steel narrow tapes

These tapes are woven with stainless steel 316L yarns. They can be supplied in different widths and lengths.

Available up to 80mm width and from 3 to 5mm thickness.

Woven in one or several layers.

Applications

Pushers covers in the hollow glass industry
They withstand very high temperature, avoid thermal shocks and micro checks which are fatal during the bottling operation.

The construction of the product makes it particularly abrasive-resistant.

These stainless steel tapes can also be used, when folded, for guiding the items on the automatic production lines

... / ...

Thermal properties

1.400°C: fusion temperature of stainless steel fiber

Chemical properties

Resistance S.S 316 L

Acid: low

Base: good

Solvent: good

Physical properties

S.S 316 L

UV resistance: good

Dielectric strength: - - - -

Product specifications (example of some dimensions)

<u>Width</u>	<u>Thickness</u>	<u>Weight / meter</u>
50 mm	3,0 mm	+/- 182 g/m
50 mm	5,0 mm	+/- 325 g/m
80 mm	3,0 mm	+/- 292 g/m

Packaging: in rolls of 50 m
Other dimensions: please contact us

Our address:

Ferlam Technologies
85, rue Monge
BP 317
59056 Roubaix cedex 1
France

Tél: + 33 (0)3 20 65 96 96
Fax: + 33 (0)3 20 65 96 99
Web site: www.ferlam.com
Contact: info@ferlam.com