



### Stainless steel vacuum pads

Made of a non woven stainless steel felt reinforced with a stainless steel scrim to improve the mechanical tenacity. Their composition and construction enable them to be resistant to very high temperatures in the most demanding conditions.

The specific fibers blending, together with the very soft contact, prevents from marking, from thermal shocks and from micro-checks.

Excellent quality - lifetime / price ratio

### Applications

- Pick and place of glass products at very high temperature

### Thermal properties

1.400°C: fusion temperature of stainless steel

### Chemical properties

|                   |                   |
|-------------------|-------------------|
| <u>Resistance</u> | <u>S.S. 316 L</u> |
| Acid:             | low               |
| Base:             | good              |
| Solvent:          | good              |

### Physical properties

|                       |                  |
|-----------------------|------------------|
|                       | <u>S.S 316 L</u> |
| <u>UV resistance:</u> | good             |

### Product specifications (example of some dimensions)

| <u>Ext.diam</u> | <u>Int.diam</u> | <u>Thickness</u> | <u>Weight / m<sup>2</sup></u> |
|-----------------|-----------------|------------------|-------------------------------|
| 110 mm          | 24 mm           | 5,0 mm           | +/- 3.900 g/m <sup>2</sup>    |
| 120 mm          | 25 mm           | 5,0 mm           | +/- 3.900 g/m <sup>2</sup>    |
| 140 mm          | 25 mm           | 5,0 mm           | +/- 3.900 g/m <sup>2</sup>    |

Packaging: box of 50 pieces  
Other dimensions: please contact us

### Nos coordonnées:

Ferlam Technologies  
85, rue Monge  
BP 317  
59056 Roubaix cedex 1  
France

Tél: + 33 (0)3 20 65 96 96  
Fax: + 33 (0)3 20 65 96 99  
Web site: [www.ferlam.com](http://www.ferlam.com)  
Contact: [info@ferlam.com](mailto:info@ferlam.com)